



LED 3W	Ra 90	2 SDCM	200 lumen	900 mA		
DIM	IP44	16 / 30 / 60° OVAL	 22 mm	2200K 2700K 3000K 4000K	L90B20 100000h	

! HUOM! Valaisimen etuosa on IP44. Takaosa on IP20. **OBS!** Armaturens framsida är IP44. Baksidan är IP20.
ATTENTION! Front of fixture is rated IP44. Back of fixture rates IP20.

	Sähkönumerot	E-Nummer	Product numbers	
saas blaze white 16	2200K	41 314 57	74 767 26	1000 2636
	2700K	41 314 59	74 767 27	1000 2637
	3000K	41 314 60	74 767 28	1000 2638
	4000K	41 314 61	74 767 29	1000 2639
saas blaze grey amber 16	2200K	41 314 74	74 767 42	1000 2654
	2700K	41 314 75	74 767 43	1000 2655
	3000K	41 314 76	74 767 44	1000 2656
	4000K	41 314 77	74 767 45	1000 2657
saas blaze black 16	2200K	41 314 66	74 767 34	1000 2646
	2700K	41 314 67	74 767 35	1000 2647
	3000K	41 314 68	74 767 36	1000 2648
	4000K	41 314 69	74 767 37	1000 2649
saas blaze white 30	2200K	41 314 62	74 767 30	1000 2640
	2700K	41 314 63	74 767 31	1000 2642
	3000K	41 314 64	74 767 32	1000 2644
	4000K	41 314 65	74 767 33	1000 2645
saas blaze grey amber 30	2200K	41 314 78	74 767 46	1000 2658
	2700K	41 314 79	74 767 47	1000 2659
	3000K	41 314 80	74 767 48	1000 2660
	4000K	41 314 81	74 767 49	1000 2661
saas blaze black 30	2200K	41 314 70	74 767 38	1000 2650
	2700K	41 314 71	74 767 39	1000 2651
	3000K	41 314 72	74 767 40	1000 2652
	4000K	41 314 73	74 767 41	1000 2653